



REACTIVATE

CARPET DESCRIPTION:	Multi Level Loop Pile
FIBRE CONTENT:	100% Solution Dyed Nylon
MACHINE GAUGE:	1/10 th gauge
FINISHED PILE HEIGHT:	4.5 mm High / 2.5mm Low +/- 1.0mm
PILE WEIGHT:	746 Grams Per Metre ² (22oz per Yard ²) +/- 5%
PRIMARY BACKING:	Woven Polypropylene
SECONDARY BACKING:	Jute / Synthetic
BACKING ADHESIVE:	SBR Latex
CARPET WIDTH:	3.66 metres (12ft Broadloom)
BOND STRENGTH:	30kgf / 50mm (30.0 Newtons)
TUFT WITHDRAWAL:	30kgf (30.0 Newtons)
PATTERN MATCH:	300mm width x 300mm length
A.C.C.S. GRADING:	Residential extra heavy duty and stairs Commercial heavy duty and stairs
INSECT RESISTANCE:	Pass
SPECIAL TREATMENTS:	Stain protection
COLOUR VARIATION:	Colour may vary from dyelot to dyelot
STATIC CONTROL:	For installations that require additional static control Feltex carpet can be treated during manufacturing.
MATERIAL VARIATION:	Backing or raw material may change without notice, depending on raw material availability.
PRODUCT VARIATION:	Variable weights and/or colours can be produced to meet individual requirements. For further details contact your local Feltex Carpets representative.

CONTACT FELTEX CARPETS:	Freephone	0800 108 008
	Freefax	0800 488 088
	Website	http://www.feltexcarpets.co.nz