



SOPRANO II

CARPET DESCRIPTION:	Tailored Level Loop
FIBRE CONTENT:	95% Wool / 5% Synthetic
YARN SPECIFICATION:	Woollen spun
MACHINE GAUGE:	1/8 th gauge (31.5/10cm)
FINISHED PILE HEIGHT:	5.5 mm +/- 1.0mm
PILE WEIGHT:	1356 Grams Per Metre ² (40oz per Yard ²) +/- 5%
PRIMARY BACKING:	Heat Stabilised Woven Polypropylene
SECONDARY BACKING:	Jute / Synthetic
BACKING ADHESIVE:	Synthetic latex
CARPET WIDTH:	3.66 metres (12ft Broadloom)
BOND STRENGTH:	30kgf / 50mm (30.0 Newtons)
TUFT WITHDRAWAL:	30kgf (30.0 Newtons)
PATTERN MATCH:	Adjoining widths must run in the same direction
GRADING:	Commercial Heavy Duty & Stairs
INSECT RESISTANCE:	Pass
SPECIAL TREATMENTS:	N/A
COLOUR VARIATION:	Colour may vary from dyelot to dyelot
STATIC CONTROL:	For installations that require additional static control Feltex carpet can be treated during manufacturing.
MATERIAL VARIATION:	Backing or raw material may change without notice, depending on raw material availability.
PRODUCT VARIATION:	Variable weights and/or colours can be produced to meet individual requirements. For further details contact your local Feltex Carpets representative.

CONTACT FELTEX CARPETS:	Freephone	0800 108 008
	Freefax	0800 488 088
	Website	http://www.feltexcarpets.co.nz