








Technical Specifications

Description	Printed Loop Pile Carpet Tile
Fibre content	100% BCF Nylon
Pile weight	746g/m ² 22oz/yd ² +/- 5%
Machine gauge	48.0/10cm 1/12th
Tile thickness	7.6mm +/- 1mm (pile thickness 3.6mm)
Backing structure	Recycled modified composite
Tile size	500mm ²
Design direction 1/4 turn recommended	Directional  1/4 Turn  Brick  Ashlar  Random 
Availability options	Cushion backed Minimum quantities apply
Country of origin	Australia

Performance

Quality assured	Manufactured under an independently certified Quality Management System ISO9001
Flammability	Result - mean 8.0kw/m ² (direct stick) Smoke value 261% minimum (direct stick)
Electrostatic propensity	Less than 3.5kv
Light reflection values	Results available on request
Stain treatment	Stainguard™
Biocontaminant control	Anti-microbial treated
Performance rating	Suitable for commercial use The grading result for Symmetry is ACCS Contract extra heavy duty 4* and stairs; ACCS registration label # 10259
Tolerances	As per AS1385 or +/- 5% (whichever is greater)
Warranty	15 year limited warranty*

Sustainability

Green Star NZ	Symmetry Feltex Tile achieves points under the Green Star rating tool
PVC minimisation	Feltex Tile is 100% PVC free
Adhesive	Feltex Carpets actively encourage installation companies to use a low solvent/solvent free, pressure sensitive adhesive when installing Feltex Tile. Please contact your local Feltex representative for more information
Recycled content	Symmetry Feltex Tile contains recycled content in both the face fibre and backing structure Minimum of 60% recycled content in the backing structure Average of 40% recycled content by weight of product
Indoor air quality	Green Building Council Australia and Green Label Plus Australia compliant for VOC emission rate limits†
Product stewardship	100% recyclable using a TQSCI certified post consumer recycling programme. Please contact your local sales representative for terms and conditions
Accreditation	Carpet Institute of Australia (CIAL) Environmental Classification Scheme (ECS) Level 4 Member of the Green Building Council of Australia Manufactured under an environmental and quality system certified and complying with ISO14001 and ISO9001 by an accredited certification body

Specifications are subject to manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice.
All Feltex Carpets Tile products must be installed in accordance with AS2455 (Parts 1 & 2) and in conjunction with the Feltex Carpets Tile Installation Instructions.
*Terms and conditions apply. †Test results are available on request.

Contact Feltex Carpets:

Freephone

0800 100 008

www.feltexcarpets.co.nz



Meets Green Label Plus Specifications