



HARD ROCK II

CARPET DESCRIPTION:	Level Loop Graphics
CONSTRUCTION:	Tufted
WIDTH:	3.66 metres (12ft Broadloom)
PILE CONTENT:	100% Solution Dyed Nylon
GRADING:	Commercial Extra Heavy Duty (including Stairs)
INSECT RESISTANCE:	Pass (Inherently Resistant)
GAUGE:	1/10g (39.4/10cm)
PILE HEIGHT:	4.0 ± 1.0mm
PILE WEIGHT:	750 gms/m ² (22oz/yd ²) ± 5%
PRIMARY BACKING:	Woven Polypropylene
SECONDARY BACKING:	Woven Synthetic
BACKING ADHESIVE:	SBR Latex
BOND STRENGTH:	30kgf / 50mm (30 Newtons)
TUFT WITHDRAWAL:	30 kgf (30 Newtons)
PATTERN REPEAT:	N/A
SPECIAL TREATMENTS:	Stain Protection
COLOUR VARIATION:	Colour may vary from dye lot to dye lot.
STATIC CONTROL:	For installations that require additional static control Feltex carpet can be treated during manufacturing.
MATERIAL VARIATION:	Backing or raw material may change without notice, depending on raw material availability.
PRODUCT VARIATION:	Variable weights and / or colours can be produced to meet Individual requirements. For further details contact your local Feltex Carpets Representative.

CONTACT FELTEX CARPETS: Freephone 0800 108 008
 Freefax 0800 488 088
 Website <http://www.feltexcarpets.co.nz>