



WHITBY

| | |
|-----------------------------|---|
| CARPET DESCRIPTION: | Tufted Cut Pile Hard Twist |
| FIBRE CONTENT: | 80% Wool / 20% Synthetic |
| MACHINE GAUGE: | 1/8th |
| DE-LAMINATION STRENGTH: | 30 |
| TUFT LOCK: | 10 |
| PILE HEIGHT: | 8.0mm ± 1mm |
| PILE WEIGHT: | 48oz per Yard ² ± 5% |
| PRIMARY BACKING: | Heat Stabilised Polypropylene |
| SECONDARY BACKING: | Jute |
| BACKING ADHESIVE: | Carboxylated – Styrene – Butadiene Rubber |
| CARPET WIDTH: | 3.66 metres |
| PERFORMANCE GRADING: | WONZ Commercial Heavy Duty (including stairs) WONZ Residential Extra Heavy Duty (including stairs) |
| COLOUR VARIATION: | Colour may vary from dye lot to dye lot |
| MOTHPROOF: | Meets IWS Standard (TM27/TM28) |
| FLAMMABILITY: (AS1530.3) | Ignitability Index 15 Spread of Flame Index 0 Heat Evolved Index 1 Smoke Developed Index 5 |
| INSTALLATION: | This carpet must be installed in accordance with AS/NZS 2455-1:1995, and/or as instructed by Feltex Carpets. |
| PRODUCTION OPTIONS: | Variable weights and/or colours may be produced to meet individual requirements. For further information please contact Feltex Carpets. |
| CONTACT FELTEX CARPETS: | Freephone 0800 100 008 Freefax 0800 488 088 Website www.feltexcarpets.co.nz |

MADE IN NEW ZEALAND