



## YORK STREET

CARPET DESCRIPTION:	Multi Level Loop
FIBRE CONTENT:	100% Wool
MACHINE GAUGE: (AS2111.9)	63.0/10cm (1/16 gauge)
FINISHED PILE HEIGHT: (AS2111.5)	4.5mm High – 3.5mm Medium – 2.5mm Low
PILE WEIGHT: (AS2111.11)	1356 g/m <sup>2</sup> (40oz)
PRIMARY BACKING:	Non Woven Spun Bonded Polypropylene
SECONDARY BACKING:	Jute
BACKING ADHESIVE:	Synthetic Latex
CARPET WIDTH:	3.66 metres
ACCS grading	Contract Heavy Duty suitable for Stairs Residential Extra Heavy Duty suitable for Stairs
WOOLS OF NEW ZEALAND GRADING:	Contract Heavy Duty + Stairs Residential Extra Heavy Duty + Stairs
PATTERN MATCH:	Mock match/ensure pile run in same direction
COLOURFASTNESS:	To Light 5/6 (BS1006.B02 Method 1) To Shampoo Min 3/4 (AS2111.19.2) To Rubbing Min 3/4 (AS2111.19.1)
FLAMMABILITY:	Please contact Feltex Carpets for a copy of all AS ISO 9239.1-2003 certificates.
TOLERANCES:	As per AS1385 or +/- 5% whichever is the greater. Specifications are subject to manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice.
CONTACT FELTEX CARPETS:	Freephone 0800 100 008 Freefax 0800 488 088 Website: <a href="http://www.feltexcarpets.co.nz">www.feltexcarpets.co.nz</a>