



Zoffany

CARPET DESCRIPTION:	Level Loop Pile
FIBRE CONTENT:	100% Wool
MACHINE GAUGE:	1/16 th (32/10cm)
PILE HEIGHT:	5.0mm +/- 1.0mm
PILE WEIGHT:	40oz / yd ² +/- 5%
PRIMARY BACKING:	Heat Stabilised Polypropylene
SECONDARY BACKING:	Jute
BACKING ADHESIVE:	Synthetic Latex
CARPET WIDTH:	3.66 metres
PERFORMANCE GRADING:	Contract Heavy Duty (including stairs)
PATTERN REPEAT:	Not applicable
COLOUR VARIATION:	Colour may vary from dye lot to dye lot
MOTHPROOF:	Meets IWS Standard (TM27/TM28)
COLOURFASTNESS:	To Light: 6 (ISO 105 B02 Method 1) To Shampoo: 4 (AS2111.19.2) To Rubbing: 4-5 (AS2111.19.1)
FLAMMABILITY: (AS/ISO 9239.1 2003)	Result – Mean 7.2 kw/m ² (conventional installation) Smoke Value 67% min (conventional installation)
INSTALLATION:	This carpet must be installed in accordance with AS/NZS 2455-1:1995, and/or as instructed by Feltex Carpets.
TOLERANCES:	As per AS 1385 or +/- whichever is greater
CONTACT FELTEX CARPETS:	Feltex Carpets 2-6 Crowhurst Street, Newmarket 1023 Phone: 09 529 6210 Fax: 09 529 6212 Website: www.feltexcarpets.co.nz