



LE MANS

CARPET DESCRIPTION:	Multi Level Loop
FIBRE CONTENT:	100% Wool
MACHINE GAUGE: (AS2111.9)	63.0/10cm (1/16 gauge)
FINISHED PILE HEIGHT: (AS2111.5)	3.8mm High – 3.0mm Medium – 1.0mm Low (+/- 1.0mm)
PILE WEIGHT: (AS2111.11)	1356 g/m ² (40oz) (+/- 5%)
PRIMARY BACKING:	Non Woven Spun Bonded Polypropylene
SECONDARY BACKING:	Jute
BACKING ADHESIVE:	Synthetic Latex
CARPET WIDTH:	3.66 metres
ACCS GRADING:	Contract Heavy Duty suitable for Stairs (27032) Residential Extra Heavy Duty suitable for Stairs
PATTERN MATCH:	36mm (width) x 70mm (Length) – Straight Match
COLOURFASTNESS:	To Light 5/6 (ISO 105 B02 Method 3) To Shampoo Min 4/5 (AS2111.19.2) To Rubbing Min 4 (AS2111.19.1) To Drycleaning solvent 4/5 (AS2001.4.16)
FLAMMABILITY:	(ISO9239 – 1:2003) Result – Mean 7.2kW/m ² (Conventionally Installed) Smoke Value 67% min (Conventionally Installed)
TOLERANCES:	As per AS1385 or +/- 5% whichever is the greater.

Specifications are subject to manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice.

CONTACT FELTEX CARPETS: Freephone 0800 100 008
Freefax 0800 488 088
Website: www.feltexcarpets.co.nz