



NOVARA IV

CARPET DESCRIPTION:	Tufted Level Loop Enhanced Graphics
FIBRE CONTENT:	90% Wool/10% Nylon
MACHINE GAUGE:	39.40/10cm (1/10th)
FINISHED PILE HEIGHT:	5.5mm +/- 1.0mm
PILE WEIGHT:	1360 Grams Per Metre ² (40oz per Yard ²) +/- 5%
PRIMARY BACKING:	Heat Stabilised Woven Polypropylene
SECONDARY BACKING:	Jute
BACKING ADHESIVE:	Synthetic Latex
CARPET WIDTH:	3.66 metres
TOLERANCES:	As per 'AS1385' or +/- 5% whichever the greater
PERFORMANCE GRADING:	Contract Heavy Duty incl. Stairs Residential Extra Heavy Duty incl. Stairs
FLAMMABILITY: (AS/ISO 9239.1 2003)	Double Stick Mean Critical Radiant Flux 8.8KW/m ² Double Stick Mean Smoke Development Rate 90% min
COLOUR VARIATION:	Colour may vary from dye-lot to dye-lot
CONTACT:	Freephone 0800 100 008 Freefax 0800 488 008 Website: www.feltexcarpets.co.nz

MADE IN NEW ZEALAND