



PROCESSOR II

CARPET DESCRIPTION:	Level loop graphic
FIBRE CONTENT:	90% Solution dyed nylon 10% Space dyed nylon
MACHINE GAUGE:	39.45/10cm (1/10 th)
PILE HEIGHT:	3.8mm +/- 1.0mm
PILE WEIGHT:	20oz per Yard ² +/- 5%
PRIMARY BACKING:	Heat stabilised woven polypropylene
SECONDARY BACKING:	Jute
BACKING ADHESIVE:	Synthetic Latex
CARPET WIDTH:	3.66 metres
ACCS GRADING:	Contract extra heavy duty inc. Stairs (registration number 28235)
ENVIRONMENTAL:	Processor II complies with ACCS Environmental Specifications
PATTERN MATCH:	45mm width x 45mm length
ELECTROSTATIC RATING:	Step 1500V Scuff 2200V
FLAMMABILITY:	AS/ISO9239.1 2003 direct stick method Mean critical radiant flux 4.5KW/m ² Mean smoke development rate 206% min
	Our sales staff will be pleased to supply you with a copy of AS/ISO9239.1 2003 certificates.
TOLERANCES:	As per AS1385 or +/- 5% whichever is the greater
CONTACT FELTEX CARPETS:	Freephone 0800 100 008 Freefax 0800 488 088 Website: www.feltexcarpets.co.nz